

## Material Safety Data Sheet Stix<sup>®</sup> Spray MOD

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	B

### SAFETY DATA

#### Manufacturer's Name:

XL Brands  
198 Nexus Drive  
Dalton, GA 30721  
1-800-367-4583

#### 24-hour Emergency:

Chemtrec 1-800-424-9300

#### Product Identification:

Product Class: Aqueous Spray Adhesive  
Product Name: Stix Spray MOD

#### Hazardous Ingredients: None known

*\*All components of this product appear on the Inventory of Chemical Substances published by the U.S. Environmental Protection Agency (EPA) under the authority of the Toxic Substances Control Act (TSCA).*

#### Physical Data:

Boiling Point: 212° F  
Vapor Density: Same as water  
Evaporation Rate: Same as water  
Appearance: Green milky liquid  
Odor: Mild characteristic  
Weight per Gallon: 8.0 lbs. typical  
pH: 9.0 typical  
Solubility in Water: Not soluble (dispersible)  
VOC (grams per liter): "Zero" calculated  
SCAQMD Rule 1168: Compliant

#### Fire and Explosion Hazard Data:

Flammable Limits: Non-flammable  
Flash Point: > 212° F  
Flammability Classification:  
OSHA: None, DOT: None  
Extinguishing Media:  
CO<sub>2</sub>, chemical foam, water fog

#### Special Fire Fighting Features:

Wear self-contained breathing gear when in confined area

#### Health Hazard Data:

Threshold Limit Value: Not established  
Effects of Overexposure: No known chronic overexposure effects

#### Emergency and First Aid Procedure:

Eye Contact: May cause irritation.  
In case of eye contact, flush with water for 10–15 minutes. If irritation persists, consult a physician.

Skin Contact: Prolonged contact may cause slight irritation of the skin. Wash with soap and water. If swallowed, consult a physician.

Inhalation: If symptomatic, move to fresh air. Get medical attention if symptoms occur.

#### Reactivity Data:

Conditions to Avoid: Excessive heat or cold  
Stability: Stable  
Incompatibility: None known  
Hazardous Decomposition Products: None known; Normal (CO<sub>2</sub>, CO)  
Hazardous Polymerization: Will not occur

#### Precautions for Handling and Use:

Ventilation: Local ventilation  
Protective Gloves: Recommended  
Eye Protection: Safety glasses  
Hygienic Practices: Wash with soap and water after exposure  
Respiratory Protection: Not required with adequate ventilation  
Other Protective Equipment: None  
Spills: Cover small spills with inert absorbent, then sweep up and place in waste disposal container. Dispose of in accordance with Federal, State and Local regulations.

#### Special Precautions/Other Comments:

Precautions to be taken in handling and storing: Store inside at a temperature of 60°–100° F. Do not allow product to freeze.

**Propellant:** UN1066 (nitrogen)  
Non-flammable compressed gas

#### Transportation Data:

D.O.T. Hazard Class: 2.2 – Shipments exceeding 1,000 lbs. must be placarded. Surface transportation only.